D21 4G LTE USB WiFi Dongle



Yifan Industry Co., Ltd

Room618, No.12 Gaodian Road, HuLi District, Xiamen, FuJian, China Tel:+86 592 6101492

Fax:+86 592 5222813

Email: admin@yifanwireless.com



1. Overview

Yeacomm D21 is a high-speed USB Wi-Fi modem router. It is a multi-mode wireless terminal.

The D21 supports the following standards:

- ♦ Wireless access is available on both 3G&4G network.
- ♦ Internet connection sharing, up to 8-10 users can access the Wi-Fi network at the same time.
- Work with external power supply, no limited working time.
- ♦ CAT4 150 Mbps DL / 50 Mbps UL speed.
- Standard USB 2.0 compatible Tabletm, Laptop, notebook, power bank, car&phone charging.
- ♦ One-touch connection.







2.Detail Specification

| Basic Product Information | Description | Remark |
|---------------------------|-----------------------------------|--|
| Model | D21 | 4G Wi-Fi dongle |
| | FDD-LTE | B1/3/5/8 (B1/3/7/8/20, B1/3/5/7/8/28, |
| | | B2/4/5/12/13/17/25/28/66 Optional) |
| Frequency | TDD-LTE | B38/39/40/41 |
| | UMTS/WCDMA/HSPA/HSPA+ | B1/2/5/8 |
| | GSM | 850/900/1800/1900Mhz |
| | TDD-LTE | 150Mbps DL/50Mbps UL |
| Speed | FDD-LTE | 150Mbps DL/50Mbps UL |
| | UMTS/WCDMA/HSPA/HSPA+ | 21Mbps DL/5.76Mbps UL |
| | | Modes supported: |
| | | 802.11b mode |
| | | 802.11g only mode |
| | 2.4GHz, 802.11b/g/n up to 150Mbps | 802.11n only mode |
| Wi-Fi | | 802.11b/g only mode |
| | | 802.11b/g/n mode |
| | | 802.11n 1*1(2.4GHz, 20MHz) |
| User amount | Max to 10 users | |



| | | 1 |
|--------------------|--|---|
| AP Features | Security modes | Open WEP WPA-PSK WPA2-PSK WPA2-PSK WPA-WPA2 Hybrid mode(Mixed Mode) TKIP-CCMP Hybrid mode(Mixed Mode) WPS 2.0 Hidden SSID supported |
| | Concurrency (FC quality for LE1.0) | AP-STA mSSID (AP-AP) – up to 2 SSID's STA-STA communication block/allow between two SSIDs Independent security modes (Open, WEP, WPA, WPA2, WAPI) for concurrency modes above except WEP in both interfaces Channel of operation - same channel |
| | Other | QoS and PS WMM WMM-PS/uAPSD ERP protection Coexistence LTE coexistence (static channel selection) Data Switching/Forwarding Switching of packets amongst clients Support for forwarding data to and from WAN VPN Pass-through |
| ♦ Interface | | |
| Antenna | 4G/3G/2G Main antenna 4G MIMO/3G Rx Diversity antenna WiFi antenna | Internal |
| USB | Standard USB 2.0 | USB 2.0 High Speed |
| SIM/USIM Card slot | Yes | Standard 6 PIN SIM card interface, compliant with 3GPP 31.101 and 31.102 |
| Micro-SD Card slot | Yes | Micro-SD Card |
| L*H*W(mm) | 96*34*12mm | |
| Weight(g) | 32g | |
| ♦ LTE | | |
| | | |



| Power | Red | |
|----------------------|--------------------------------|--|
| Wi-Fi | Green | |
| LTE | Blue | |
| ♦ Other Description | | |
| RF Power Spec | Class 4 for UMTS/HSPA/LTE; | |
| | Class 4 for GSM 850/900; | |
| | Class 1 for GSM 1800/1900; | |
| | Class E2 for EDGE | |
| | 850/900/1800/1900 | |
| Power Supplu Input | USB 2.0 5V-1A | |
| ♦ Software | | |
| UI | WEB UI | |
| Operation system | Windows / Mac OS /IOS/ Android | |
| Operation | Internet Explorer/Mozilla | |
| | Firefox/Google Chrome/Safari | |
| ♦ Environmental | | |
| Normal Operation | 0°C to +45°C | |
| Restricted Operation | -10°C to +55°C | |
| Storage | -20°C to +70°C | |
| ♦ Certificate | | |
| ROHS | Compliance | |
| CE | Compliance | |

Selection and Ordering Data

D21 Series modem

| . Descriptio | Model No. |
|--------------------------|-----------|
| 4G LTE WIFI Mode | D21 |
| 4G LTE modem(without WIF | D21-N |